

**CS1082EG-POE**

## Unmanaged Ethernet PoE Switch

**8FE + 2GE**

### Brief Views

The PoE switch provides power and data from a single point, using Power over Ethernet (PoE) over a single Cat-5 cable. It provides 8\*10/100Mbps PoE ports and 2\*1000Mbps Uplink ports. It supports IEEE 802.3af/at standards. Advanced auto-sensing algorithm gives power to 802.3af/at end devices, In addition, the PoE switch automatically determines PoE requirements, speed, duplex, and cable type using Auto Uplink. Easy to operate and reliable.

The PoE switch is ideal for powering PoE devices such as IP cameras, WLAN access point, IP phones, office access control systems, and other PD devices and offers a line of high quality products that provide a total solution for Ethernet application in different environments.

### Functional Features

- 8\*100mbps POE RJ45 Auto MDI/MDIX ports;
- 2\*1000M RJ45 Auto MDI/MDIX ports ;
- Support watchdog,VLAN,Extend (DIP) ;
- Compatible with IEEE802.3AF/AT ;
- Max Power:120W ;
- Each port max. power supply reached 30W ;
- Supply 8pcs 10/100Mbps adaptive high speed forwarding data packet non-lost port ;
- Low heat design, safe and reliable, high stability.

## Hardware

- **Downlink ports**
  - 8\*10/100M BASE-T RJ45
- **Uplink ports**
  - 2\*10/100/1000M BASE-T RJ45
- **Switching capability**
  - 5.6Gbps
- **Packets switching capability**
  - 6.65Mpps
- **Switching method**
  - Storage forwarding
- **LED light**
  - PWR ( power supply )
  - SW ( DIP )
  - 1-10 Green ( Link&Data )
- **Enviroment parameters**
  - Work temperature : -10 - to 50°C
  - Storage temperature : -40 - 70°C
  - Work humidity : 10% to 90%
  - Storage humidity : 10% to 90%
- **MAC table size**
  - 2K
- **Input Power**
  - Input: 100-240V AC, 50/60Hz
- **PoE Power**
  - Max Power:120W
  - PoE Standard: IEEE802.3af/at
  - Max. 30W output of single PoE port
- **Dimention ( W\*D\*Hmm )**
  - 200\*118\*44 mm
- **Weight**
  - N.W:0.6Kg G.W:0.9Kg
- **Certification compliance**
  - FCC CE ROHS
- **Installation**
  - Desktop